

Standard	Result
Thickness	4.5 mm
Size	See page 2
Wear layer	20 mil (0.50 mm)
Surface treatment	PU coating
Warranty ¹	15 Years
	Lifetime
Beveled edge	No
Classification	Class III Type B
Reaction to fire	Class 1
Smoke Density	Pass (< 450)
Flammability test	Pass
Slip resistance ²	Dry 0.92
Staining resistance	Pass
Light fastness	Pass ($\Delta E = 1.7$)
Abrasion resistance	113,000 Cycles
Dimensional stability	Pass (0.0045"/lin.ft)
Acoustic impact noise reduction	$\Delta IIC = 16 \text{ dB}$
	IIC = 56 dB (6" Concrete Slab w/Drop Ceiling)
	IIC = 71 dB (6" Concrete Slab w/Drop Ceiling + QuietChoice)
Static load	1,000 psi
Flexibility	Pass
Electrostatic propensity	Pass
Adhesive	DrySet
	K-Spray
	Karndean Epoxy
	K99 HM
Environmental	Certified
	Type III EPD
	Silver certified product
	Manufactured in certified facilities
Recycling	Suitable
Phthalate free	Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



Plank/Tile	Size (in)	Size (mm)	Box qty (ft ²)	Box qty (pieces)
Plank	41.34" x 9.84"	1050.0 x 250.0	33.91	12